



installation instructions

performance spark plug wires for 1999/2002 ducati 750/900ss

part number 80050

©2006, 2002, 2001 by evoluzione.net, inc.

these **evoluzione cyclesports performance spark plug wires** are specifically designed to work with the computerized ignition found on the late model supersports. these wires feature a 7mm silicone jacket and solid copper conductor. also included with the kit is ngk wide gap spark plugs. this kit will allow you to take full advantage of your ducati's ignition system.

introduction

the **evoluzione cyclesports performance spark plug wires** are easy to install by carefully following the instructions. read all instructions first to familiarize yourself with the parts and procedures.

installation

caution: It is suggested that the

bike be allowed to cool off for a few hours to avoid burns from hot exhaust and parts.

step 1. using 3mm & 4mm allen wrenches, remove the left side fairing.

step 2. pull the spark plug wire lead off of the vertical (rear) cylinder spark plug. using a 5/8" spark plug wrench, remove the spark plug. using an 18mm spark plug wrench, install one of the supplied ngk spark plugs.

step 3. using a pair of wire cutters, remove the tie wrap(s) holding the vertical cylinder spark plug wire to the frame. with a twisting motion, remove the spark plug wire from the coil. match this wire to the same length wire supplied in the kit. install the black boot of the new wire on to the coil (make sure it fully seats) and route the wire along the frame, attaching it with

the supplied tie wraps. insert the red boot over the spark plug, making sure it fully seats.

step 4. repeat steps two & three for the horizontal (front) cylinder.

step 5. replace the left fairing.

parts list

performance plug wires (16")
performance plug wires (20")
ngk performance plugs (2)
6" tie wraps (4)

tools required

3mm & 4mm allen wrenches
5/8" & 18mm plug wrenches
wire cutters