

evoluzione cyclesports

installation instructions

performance spark plug wires for 1991/1998 ducati 750/900ss & 1994/2005 ducati monster exc. s4, s4r, m1000

part number 80051

©2006, 2005, 2002, 2001 by evoluzione.net, inc.

these **evoluzione cyclesports performance spark plug wires** feature an 7mm silicone jacket and solid copper conductor. also included with the kit is ngk wide gap spark plugs.

introduction

the **evoluzione cyclesports performance spark plug wires** are easy to install by carefully following the instructions. [read all instructions first to familiarize yourself with the parts and procedures.](#)

installation

caution: It is suggested that the bike be allowed to cool off for a few hours to avoid burns from hot exhaust and parts.

step 1. using 3mm & 4mm allen wrenches, remove the left side fairing. remove the seat and lift the fuel tank and place on it's prop rod.

step 2. with a 10mm wrench, disconnect both battery leads. disconnect the vent tube from the side of the battery. undo the straps and remove the battery.

step 3. pull the spark plug wire lead off of the vertical (rear) cylinder spark plug. using a 5/8" spark plug wrench, remove the spark plug. using an 18mm spark plug wrench, install one of the supplied ngk spark plugs.

step 4. using a pair of wire cutters, remove the tie wrap(s) holding the vertical cylinder spark plug wire to the frame. unscrew the collar at the base of the coil and remove the spark plug wire from the coil (note: some of these collars appear to be glued from the factory - take your time to avoid damaging the collar). carefully measure this wire then cut the shorter wire supplied in the kit to the same length. install the collar on to the new wire. gently but firmly push the wire into the base of the coil

and then turn the wire clockwise several turns to fully seat. next, tighten the collar on to the coil base. route the wire along the frame, attaching it with the supplied tie wraps. insert the boot over the spark plug, making sure it fully seats.

step 5. repeat steps three & four for the horizontal (front) cylinder using the longer of the supplied wires.

step 6. replace the battery in it's holder, reattach the straps, vent tube and battery leads.

step 7. lower the fuel tank, reinstall the seat and replace the left fairing.

parts list

performance plug wire (30")
performance plug wire (36")
ngk performance plugs (2)
6" tie wraps (4)

tools required

3mm & 4mm allen wrenches
5/8" & 18mm plug wrenches
10mm wrench
wire cutters

38580 celine cove, suite "b"
murrieta, california 92562

phone: 951.639.0951
fax: 951.639.3022

october 2006, revision 06