



installation instructions

license plate relocater for 1999/2007 ducati supersport

part number 90022

©2006, 2005, 2004, 2002, 2001 by evoluzione.net, inc.

this **evoluzione cyclesports license plate relocater** is designed to clean up the tail end look on 1999/2007 supersports models and is made from light weight 5052-h32 aluminium for long life.

introduction

the **evoluzione cyclesports license plate relocater** is easy to install by carefully following the instructions. read all instructions first to familiarize yourself with the parts and procedures.

installation

caution: It is suggested that the bike be allowed to cool off for a few hours to avoid burns from hot exhaust and parts.

step 1. remove the seat. using a 5mm allen wrench, remove the two bolts and washers from underneath the underseat tray (these bolts also hold the separator tank). also remove the two bolts and washers inside the back of the underseat tray.

step 2. carefully lower the underseat tray and rest on the rear fender.

step 3. before disconnecting the six wires (license plate illumination, right & left turnsignal), write down their connections. now disconnect the wires.

step 4. using a 4mm allen wrench, remove the five (5) bolts and washers holding the subfender to the underseat tray and set it aside.

step 5. using a 10mm wrench and 5mm allen wrench, remove both turnsignals from the subfender (mark them left and right for reassembly). also remove the license plate from the subfender.

step 6. reattach the turnsignals to the relocater bracket by feeding the turnsignal wires through the larger of the two holes on the sides of the bracket (noting left and right).

step 7. install one washer on each 5mm bolt and insert through the bracket from the underside. next install the spacers over the bolts and finally the second washers. route the turnsignal wires through the pass-through hole in the

underseat tray. with a 4mm allen wrench, attach the relocater bracket to the two rearmost wellnuts on the underseat tray (make sure the wires from the turnsignals run between the bracket and the underseat tray).

step 8. locate the rearmost (center) well nut and remove. install the supplied metal collar from underneath and secure with the lock washer and nut. install the bulb into the bulb holder and thread the assembly into the collar (from the top). thread the clear lens into the collar from underneath. connect the wires to the license plate light harness (note: the wires can be hooked up either way).

step 9. reconnect the wires from the turnsignals. using the supplied tie wraps, neatly bundle the wires.

step 10. reinstall the underseat tray, separator tank and the seat.

step 11. turn the key to "on" and check that the turnsignals and license plate light function correctly.

38580 celine cove, suite "b"
murrieta, california 92562

phone: 951.639.0951
fax: 951.639.3022

october 2006, revision 09

parts list

relocator bracket
collar with nut/washer
bulb holder w/ harness
clear bulb lens & bulb
m5 x 25mm bolts (2)
spacers (2)
washers (4)
tie wraps (2)

tools required

4 & 5mm allen wrench
10mm wrench

