

evoluzione cyclesports

installation instructions

license plate relocater for 1998/2002 aprilia rsv/rsv-r mille

part number 95020

©2006, 2005, 2002, 2001 by evoluzione.net, inc.

this **evoluzione cyclesports license plate relocater** is designed to be a lightweight, simple addition to help clean up the tail end look on the 1998/2002 aprilia rsv/rsv-r mille. the relocater bracket is made from 5052-h32 aluminium for long life and light weight. **note: due to the repositioning of the turn signals, this kit may not be legal for street use - please check local laws first.**

introduction

the **evoluzione cyclesports license plate relocater** is easy to install by carefully following the instructions. read all instructions first to familiarize yourself with the parts and procedures.

installation

caution: It is suggested that the bike be allowed to cool off for a few hours to avoid burns from hot exhaust and parts.

step 1. remove the rear seat or cover.

step 2. locate the white, two

prong left side turn signal connector (blue and light blue wires). gently pull the connection apart. locate the white, two prong right side turn signal connector (red and blue wires). gently pull the connection apart.

step 3. using an 8mm socket and 10mm wrench, remove the left and right turn signals, the plate holder bracket and the two small side reflectors.

step 4. either fully remove the rear body panel or carefully mask the lower edge with heavy tape. using a small saw (or rotary tool), cut the two lower "fins" off of the underseat tray. finish the edge off and remove the tape (please see photo one).

step 5. using the supplied brass tool, carefully remove the turn signal pins (wires) from white two prong connectors (please see photo two)

step 6. feed the turn signal wires through the larger of the two holes on the sides of the bracket and reattach the turn signals, noting left and right.

step 7. with a 4mm allen wrench, remove the two bolts holding the rear tail light housing assembly on the bottom (please see photo one).

step 8. install a supplied washer on each of the supplied 5mm bolts. insert the bolts through the end holes of the bracket (from the bottom). install a supplied washer, standoff and washer onto each bolt. thread the bolts into the two bottom mounting holes of the rear tail light housing. tighten the bolts.

step 9. reinsert the turn signal pins (wires) back into the white two prong connectors until they "snap" into place (orientation is not important).

step 10. feed the turn signal wires back through the underseat tray and reconnect to the harness.

step 11. reinstall the rear seat or cover.

step 12. remove your license plate from the stock bracket and install onto the new bracket.

step 13. turn the key to "on" and check that the turn signals function correctly.

38580 celine cove, suite "b"
murrieta, california 92562

phone: 951.639.0951
fax: 951.639.3022

october 2006, revision 05

parts list

relocator bracket
standoff (2)
5mm bolt (2)
5mm washers (6)
brass pin removal tool

tools required

8mm socket & driver
8mm & 10mm wrench
4mm allen wrench
hack saw (or rotary tool)
heavy masking tape



photo one



photo two